

AMI400

Fanless

With Intel Core™ 2 Duo support



Features

- Fanless system supports IBASE MI910E and MB899HF Mini-ITX motherboards
- One expansion slot outlet on rear panel
- Available in silver color
- One 2.5" HDD drive bay
- One expandable PCI slot
- One slim type DVD combo drive (optional)
- Fanless operation
- Wall mount kit included

Specifications

System Mainboard	MI910E & MB899HF
Construction	Aluminum & Steel
Chassis Color	Silver (Aluminum)
Front Panel External I/O	Power LED, HDD LED, Reset button power on/off button, 2x USB 2.0 ports
Rear Panel External I/O	MI910: Audio, 1x LAN, 4x USB, COM, VGA, SPDIF, 1394, KB/MS MB899: Audio, 2x LAN, 4x USB, COM, VGA, TV out, SPDIF, 1394, KB/MS
Storage	1x 2.5" HDD, optional 1x 5.25" slim type DVD combo
Expansion Slot	1x PCI
Power Supply	150W power adaptor
Mounting	Desktop or wall mount kit (wall mount kit included)
Dimensions	267mm(W) x 263.5mm(D) x 109mm(H)

Environmental

Operating Temperature	0°C ~ 45°C
Storage Temperature	-20° ~ 80°C
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 0.25 grms/5~500Hz random operation

Ordering Information

AMI400-8	Aluminum System with MB899HF, Intel® 440 (1.83GHz) CPU, 1GB DDR2, 2.5" 80GB HDD, IP115 PCI Riser Card, 110W DC-DC Converter, 150W Power Adaptor
AMI400-8C	Aluminum Chassis for MB899HF, 2.5" HDD holder, 110W DC-DC Converter, 150W Power Adaptor, IP115 PCI Riser Card
AMI400-9	Aluminum System with MI910E, Intel® T7500 (2.2GHz) CPU, 2GB DDR2, 2.5" 80GB HDD, ID392 DVI Board, IP115 PCI Riser Card, 110W DC-DC Converter, 150W Power Adaptor
AMI400-9C	Aluminum Chassis for MI910E, 2.5" HDD holder, 110W DC-DC Converter, 150W Power Adaptor, IP115 PCI Riser Card



Remarks: 2. ODM/OEM is available.

3. Specifications are subject to change without prior notice.

- 1 Motherboards
- 2 Disk-size SBCs
- 3 CPU Modules
- 4 PC/104 Puls
- 5 CPU Card
- 6 Embedded Systems
- 7 Network Security Appliance