

SI-06

Entry-Level Digital Signage Player

Intel® Atom™ Processor D2550 Fanless Signage Player with 1x Hybrid-DVI (VGA/ DVI/ HDMI with audio)

Signature Book™



Features

- iSMART - for EuP/ErP power saving, autoscheduler and power resume
- Onboard Intel® Atom™ Processor D2550 (Low power consumption)
- Intel® GMA 3650 integrated graphics
- 1x DDR3 1066MHz SO-DIMM, Max. 4GB
- 1x Mini PCI-E (Full-size) for mSATA, Wi-Fi, Bluetooth, 4G, or TV tuner options
- Fanless and compact design

Specifications

System Mainboard	IB901
CPU Type	Intel® Atom™ Processor D2550
CPU Package	FCBGA559
Chipset	Intel® NM10
Memory	1x 204-pin SO-DIMM socket, supports DDR3 1066MHz with unbuffered and non-ECC memory module, Max. 4GB
Graphics	Intel® GMA 3650 integrated graphics engine
LAN	1x Realtek RTL8111E PCI-E Gigabit LAN controller
Expansion Slots	1x Mini PCI-E (Full-size) for mSATA, Wi-Fi, Bluetooth, 4G, or TV tuner options
I/O Interface	2x USB 2.0 ports 1x RJ45 for Gigabit LAN 1x RJ45 for RS232 1x Hybrid-DVI (VGA/ DVI/ HDMI with audio) 1x Microjack audio connector for speaker Power LED / HDD LED, power on/off button 12V DC-in power connector
Auto Control and Monitoring	Watchdog Timer: 256 segments, 0, 1, 2...255 (sec/min) On / Off scheduler: 2 time slots
Power Requirement	+12V DC-in
Construction	Aluminum + SGCC
Weight	1.26KG (2.77lbs)
Chassis Color	Black & white
Storage	1x 2.5" HDD drive bay
Power Supply	40W power adaptor
Mounting	Slim design with wall mounting holes
Dimensions	166mm(W) x 102mm(D) x 34mm(H) 6.54"(W) x 4.02"(D) x 1.34"(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C ~ 80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	SSD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation
Certification	CE, FCC class B, cULus & CCC
Operating System	Windows XP, Win7 32/64-bit, Win8 64-bit, Win8.1 64-bit Win10 64-bit Enterprise (Upgrade Only)

Ordering Information

SI-06	Signage Player with 2GB RAM, 320GB HDD, 40W power adaptor
SI-MK1	Mounting bracket for SI-06/08/12/18/22 series

Dimensions

