



Features

- Onboard 7th Gen Intel® Core™ i7/i5/i3 processors
- 2x DDR4 SO-DIMM, Max. 32GB
- Supports 2x DDI port or DDI + VGA
- 1x Intel® PCI-E GbE LAN
- Watchdog timer
- 8x USB 2.0, 4x USB 3.0, 2x COM, 2x SATA III
- 4x PCI-E(x1), 1x PCI-E(x4)
- Supports TPM (2.0), eMMC5.0 (optional)

Specifications

| | |
|------------------------|--|
| CPU Type | Onboard 7th Gen Intel® Core™ U-series processors |
| System Memory | 2x DDR4 SO-DIMM, Max. 32GB |
| System Chipset | N/A |
| BIOS | AMI |
| Watchdog Timer | 256 levels |
| SSD | eMMC 5.0 up to 32GB (optional) |
| H/W Monitor | Yes |
| Expansion Slot | 4x PCI-E(x1), 1x PCI-E(x4) |
| VGA Controller | 7th Gen Intel® Core™ U-series processor integrated graphics, supports DVI, HDMI, DisplayPort, LVDS |
| VGA Memory | Shared memory |
| Display Interface | 24-bit dual-channels LVDS on carrier board |
| LAN Controller | Intel® I219LM LAN PHY |
| LAN Connector | 1x RJ-45 on carrier board (IP413) |
| I/O Chipset | Nuvoton NCT5523D on board (supports Tx/Rx only) |
| USB | 4x USB3.0 via baseboard 8x USB2.0 via baseboard |
| Serial ATA | 2x SATA III via carrier board |
| Audio | 7th Gen Intel® Core™ U-series processor built-in HD Audio |
| Others | TPM (2.0) |
| Dimensions | 95mm x 95mm (3.74" x 3.74") |
| Max. Power Requirement | Intel® i7-7600U, 2.8GHz w/8GB DDR4-2133 +12V: 3.47A; +5V: 1.4A +3.3V: 0.33, +5VBS: 0.10A |
| Operating Temperature | -20°C~60°C (-4°F~140°F) |
| Storage Temperature | -20°C~80°C (-4°F~176°F) |
| Relative Humidity | 10% ~ 90% (non-condensing) |

Ordering Information

| | |
|-----------------|---|
| ET975K-i7 | COM Express (Type 6) CPU Module w/ Intel® Core™ i7-7600U, DDR4 dual-channel memory, 2x DDI |
| ET975K-i7V | COM Express (Type 6) CPU Module w/ Intel® Core™ i7-7600U, DDR4 dual-channel memory, 1x DDI+ 1x VGA |
| ET975K-i7e32 | COM Express (Type 6) CPU Module w/ Intel® Core™ i7-7600U, DDR4 dual-channel memory, 2x DDI, eMMC 32GB |
| ET975K-i7Ve32 | COM Express (Type 6) CPU Module w/ Intel® Core™ i7-7600U, DDR4 dual-channel memory, 1x DDI+ 1x VGA, eMMC 32GB |
| ET975K-i5 | COM Express (Type 6) CPU Module w/ Intel® Core™ i5-7300U, DDR4 dual-channel memory, 2x DDI |
| ET975K-i5V | COM Express (Type 6) CPU Module w/ Intel® Core™ i5-7300U, DDR4 dual-channel memory, 1x DDI+1x VGA |
| ET975K-i5e32 | COM Express (Type 6) CPU Module w/ Intel® Core™ i5-7300U, DDR4 dual-channel memory, 2x DDI, eMMC 32GB |
| ET975K-i5Ve32 | COM Express (Type 6) CPU Module w/ Intel® Core™ i5-7300U, DDR4 dual-channel memory, 1x DDI+1x VGA, eMMC 32GB |
| ET975K-i3 (MOQ) | COM Express (Type 6) CPU Module w/ Intel® Core™ i3-7100U, DDR4 dual-channel memory, 2x DDI |
| ET975S-i7 | COM Express (Type 6) CPU Module w/ Intel® Core™ i7-6600U, DDR4 dual-channel memory, 2x DDI |
| ET975S-i7V | COM Express (Type 6) CPU Module w/ Intel® Core™ i7-6600U, DDR4 dual-channel memory, 1x DDI+1x VGA |
| ET975S-i7e32 | COM Express (Type 6) CPU Module w/ Intel® Core™ i7-6600U, DDR4 dual-channel memory, 2x DDI, eMMC 32GB |
| ET975S-i7Ve32 | COM Express (Type 6) CPU Module w/ Intel® Core™ i7-6600U, DDR4 dual-channel memory, 1x DDI+1x VGA, eMMC 32GB |
| HSET975-A | Heatsink with Fan for ET975 |
| HSET975-1 | Heat Spreader for ET975 |

Dimensions and Drawing

